

# WASHER EXTRACTORS

TWE 10 · 15 · 18



## STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing
- Water inlet hoses
- Steam inlet hose

## OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- High flow inlet valves for faster filling
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Chemical hold signal
- Integrated plinth to increase loading height and ensure ergonomic operation and fit linen carts (Height 160 mm to reach bottom loading door of 700 mm)

TOLON

# WASHER EXTRACTORS

## TWE 10 · 15 · 18

MODEL	UNIT	TWE 10	TWE 15	TWE 18
Dry load	lb	22	33	39.6
Performance	lb/h	33	49.5	59.4
Cycle time	min	30-45	30-45	30-45
<b>DRUM</b>				
Drum diameter	inches	24.8	24.8	24.8
Drum depth	inches	13	19.3	22.8
Drum volume	ft <sup>3</sup>	3.6	5.4	6.4
Wash speed	rpm	43	43	43
Extraction speed	rpm	1012	1012	1012
G-force		360	360	360
<b>DOOR</b>				
Door opening Ø	inches	18	18	18
<b>HEATING</b>				
Electric	kW	9	15	18
Steam	psi	58-87	58-87	58-87
<b>ELECTRIC</b>				
Electric consumption*	kWh	2.34	3.10	3.66
Motor	HP	2.01	2.95	4.02
<b>STEAM</b>				
Steam valve connection Ø	DN-BSP	15-½"	15-½"	15-½"
Steam pressure	psi	58-87	58-87	58-87
Steam consumption	lb/cycle	11	16.5	19.8
<b>AIR</b>				
Air connection Ø	inches	optional / 0.24	optional / 0.24	optional / 0.24
<b>WATER</b>				
Inlet valve connection Ø	DN-BSP	2 x 20-¾"	2 x 20-¾"	2 x 20-¾"
Water inlet (detergent) Ø	DN-BSP	-	-	-
Water pressure	psi	29-58	29-58	29-58
Water flow	gal/min	15.9	15.9	15.9
Water consumption*	cold gal/cycle	10.30	15.30	17.96
	hot gal/cycle	11.10	16.40	19.28
Drain valve connection Ø (outer)	inches	3	3	3
Drain flow	gal/min	60.8	60.8	60.8
<b>PROGRAMMABLE CONTROL</b>				
16 default programmes (max. 99)		Std	Std	Std
7" colour, high-resolution LCD		Std	Std	Std
<b>DIMENSIONS (WxDxH)</b>				
Standard	inches	34.6 x 38.4 x 59.1	34.6 x 44.7 x 59.1	34.6 x 48.3 x 59.1
Standard with plinth	inches	34.6 x 38.4 x 67.3	34.6 x 44.7 x 67.3	34.6 x 48.3 x 67.3
Packing	inches	36.6 x 40.9 x 61	36.6 x 47.2 x 61	36.6 x 51.2 x 61
Packing with plinth	inches	36.6 x 40.9 x 69.3	36.6 x 47.2 x 69.3	36.6 x 51.2 x 69.3
<b>WEIGHT</b>				
Net	lb	964	1019	1047
Net with plinth	lb	1012	1069	1100
Gross	lb	1012	1074	1109
Gross with plinth	lb	1155	1190	1265
<b>SOUND LEVEL</b>				
	db(A)	55-65	55-65	55-65

\* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

[www.tolon.com](http://www.tolon.com)

TOLON