

IRONERS

TFI 6026 · 6032



STANDARD FEATURES & BENEFITS

- Ergonomic cylinder heated ironer
- Gas or electric heating
- Extended heat transfer path
- Large surface contact with linen
- Roll standard with chrome surface coating for better thermal conduction and highly resistant to corrosion, even after periods of inactivity
- With a pressure roll for perfect ironing quality
- Finger protection panel and emergency button for more safety
- Easy to use electronic control with pre-set ironing programmes
- Indication of ironing temperature and speed
- Frequency controlled motor
- Reverse mode possible
- Space-saving wall model with front return of the linen
- Overheating check system with 3 temperature sensors
- Automatically adjusted ironing speed, based on humidity of the linen
- Premix burner for more power and efficient ironing
- LED lights on the ironing width for good visibility and operation

OPTIONS

- Longitudinal fold
- 3 folding sensors at feeding point instead of 1
- Transport wheels
- Rear output of the linen

TOLON

IRONERS

TFI 6026 · 6032

MODEL	UNIT	TFI 6026	TFI 6032
Roll diameter	in	23.62	23.62
Working width	in	102.3	126
Roll speed	in/min	0.137-0.472	0.137-0.472
Performance* Electric folding	lb/h	319-357	397-441
HEATING			
Electric			
Electric heating power **	kW	56	69
Evaporation	gal/h	17	21
Electric consumption	kW/h	57.8	71
Gas			
Gas heating power	kW	65	80
	Btu	221789	272971
Evaporation	gal/h	21.1	26.4
Gas connection Ø	DN/BSP	20 (¾")	20 (¾")
Gas pressure	psi	0.30-0.87	0.30-0.87
Gas consumption	kW/h	56	84
	Btu/h	190350	287320
VOLTAGE/ELECTRIC CONNECTION			
Electric			
		380-415V 3ph + N 50Hz	
		380-415V 3ph + N 60Hz	
		440-480V 3ph 50Hz	
		440-480V 3ph 60Hz	
Gas			
		380-415V 3ph + N 50Hz	
		380-415V 3ph + N 60Hz	
		440-480V 3ph 50Hz	
		440-480V 3phN 60Hz	
		200-240V 3ph 50Hz	
		200-240V 3ph 60Hz	
		200-240V 1ph 50/60Hz	
MOTORS			
Roll motor	hp	1.019	1.019
Fan motor	hp	1.49	1.49
EXHAUST			
Exhaust connection Ø	in	4.92	4.92
Airflow			
Electric	ft³/h	39729	39729
Gas	ft³/h	39729	39729
DIMENSIONS (WxDxH)			
Standard	in	139.8 x 53.18 x 62.91	163.46 x 53.18 x 62.91
Standard rear exit model	in	139.8 x 64.84 x 62.91	163.46 x 64.84 x 62.91
Packed	in	143.7 x 59 x 69.21	167.32 x 59 x 69.21
Packed rear exit model	in	143.7 x 70.87 x 69.21	167.32 x 70.87 x 69.21
WEIGHT			
Net	lb	4023	4431
Gross	lb	4354	4894
SOUND LEVEL			
	db(A)	< 65.6	< 65.6

* 50% moisture - folding at 0.354 in/min

** Output calculated at 380V/IIIphase

TOLON reserves the right to make changes to the machines and the specifications in this datasheet at any time, without prior notice. Details and photographs are only for informational purposes and are never binding.

www.tolon.com

TOLON