

TUMBLE DRYERS

TRD 28 · 33



STANDARD FEATURES & BENEFITS

- Tumble dryer in skin plate, cream color
- Big loading door (opening of 180°)
- Transmission by pulley and belt
- Time and temperature selection
- Reverse drum: all models offer the reverse turning of the drum
- Drum in galvanised steel
- Digital control and electronic control. Easy and intuitive to use, the electronic control offers a complete control of the process
- Radial airflow circuit
- New filter drawer with wide surface and improved airflow, filter grid is standard 0,3 mm
- Cool down: anti-wrinkle at the end of cycle
- Models available in electric, gas or steam heating
- Self-Service: Digital range has several payment options for laundromats; to work with centralized payment systems, with coin / token, or with prepaid card systems. Electric and gas heated models for self-service available

OPTIONS

- Moisture control
- Double doorglass
- Stainless steel drum with mixed axial-radial flow and punched drum holes
- Stainless steel body
- Stainless steel front panel
- Low pressure steam battery
- Opposite door opening
- Lint filter with dia. 0,6 or 1,2 mm mesh
- Wooden box packing
- Special voltages
- Mechanical meter for coin / token
- Electronic coin kit
- Prepared for central payment

TOLON

TUMBLE DRYERS

TRD 28 · 33

MODEL	UNIT	TRD 28	TRD 33
Capacity 1/18	lb	60	75
Capacity 1/20	lb/h	131	141
Evaporation capacity *	l/h	30.9	32.1
DRUM			
Ø Drum	in	37.3	37.3
Ø Door	in	31.6	31.6
Center door height	in	41	41
Bottom door height	in	25.2	25.2
Drum depth	in	30.7	36.9
Drum volume	ft ³	19.4	23.3
POWER			
Drum motor	HP	0.74	0.74
Fan motor	HP	0.74	0.74
Electric heating	kW	30	36
Total electric power (elec. model)	kW	31.2	21.2
Gas heating	BTU	139898	139898
Steam heating	kW	50.1	50.1
CONNECTIONS		ELECTRICAL - STEAM/GAS	ELECTRICAL - STEAM/GAS
Tension 230V - I + N + T	No x mm ² / A	- - 3 x 1.5 / 20A	- - 3 x 1.5 / 20A
Tension 230V - III + T	No x mm ² / A	4 x 35 / 100A - 3 x 1.5 / 20A	4 x 50 / 125A - 3 x 1.5 / 20A
Tension 400V - III + N + T	No x mm ² / A	5 x 16 / 63A - 3 x 1.5 / 20A	5 x 16 / 63A - 3 x 1.5 / 20A
Ø Gas inlet	BSP	1/2"	1/2"
Ø Steam inlet	BSP	1"	1"
Ø Condensed (Steam models)	BSP	1"	1"
DIMENSIONS / PACKING DIMENSIONS			
Net Width / Gross Width	in	38.8 / 42	38.8 / 42
Net Depth / Gross Depth	in	41.5 / 45.5	41.5 / 51
Net Height / Gross Height	in	77.8 / 82	77.8 / 82
Net Weight / Gross Weight	lb	507 / 573	573 / 628
OTHERS			
Max airflow	CFM	706	706
Ø Fume exhaust	in	8	8
Sound level	dB	65	65

* It may vary depending on the type of heating, filter cleanliness or extraction type.

Given values are for gas.